



Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

This document defines the interpretation of the BankToCustomerDebitCreditNotificationV02" Camt.054 as described by the ISO 20022 - camt.054.001.02 standard.

Please note that reporting on Swedish accounts is implemented on Danske Banks interpretation as no country specific recommendations have been published yet.

Files produced and received from Danske Bank will adhere to these standards and will be valid according to the XML Schema for camt.054.001.02 as published on the <http://www.iso20022.org> website.

For further information about the Common Global Implementation initiative please refer to <http://www.swift.com/cgi>

The description only includes tags used by Danske Bank. Blank fields in the Danske Bank column means that the content in the message applies to the usage as described in the ISO Definition and/or in the CGI Rules column.

XML Header

The XML Header should follow the recommendation from www.iso20022.org:

```
<?xml version = "1.0" encoding = "UTF-8"?>
```

```
<Document xmlns = "urn:iso:std:iso:20022:tech:xsd:camt.054.001.02" xmlns:xsi = "http://www.w3.org/2001/XMLSchema-instance">
```

The interpretation includes information in the form of a table. ISO-columns refers to the official description from ISO 20022 Payments - Maintenance 2009 Message Definition Report. Danske Bank-columns contains the interpretation made by Danske Bank. There are tags that are not used by Danske Bank - but still has to be specified to adhere to the ISO standard.

Character set

The following character set can be used: UTF-8

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

The table below explains the usage of the columns.

Column Header	Content
ISO Index No.	The index used by ISO in the official description of Payments Standards – Initiation
Item	The corresponding ISO-name of the tag (full name) followed by the cardinality. [0..1] means that the tag is optional – there can be either zero or one instance of the tag. [1..1] means mandatory field – one occurrence. [0..n] means optional field – there can be from zero to many occurrences.
Tag-name	The name of the XML-tag preceded by a number of plus (+) signs showing the nested level the tag is used on
Mult.	(0..1) – Element is optional (1..1) – Element is required (0..n) – Optional with unlimited repetition (1..n) – Required with unlimited repetition
Type	The content type of the tag. See – Data Types.
ISO Definition	Contains the ISO definition for the item.
Codes	R/M = Mandatory field, C= Conditional (or optional)
CGI comments	CGI rules - specific limitations and naming of the content
Danske Bank Comments	Other comments that may be helpful when reading camt files from Danske Bank
Country Specific interpretation	Information regarding country specific usage if it differs from the standard reporting



Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

Data types	
Type	Description
Text	Text in Unicode Format
Component	A block of information consisting of different message elements.
DateTime	ISO date/time format.
Number	Numeric form
Code	ISO Code
Amount	Amount of money with currency specified as an XML attribute called Ccy
Identifier	Format depends on the context
Rate	Rate expressed as a decimal, eg, 0.7 is 7/10 and 70%. Format: fractionDigits: 10, totalDigits: 11

Colour/Background	Meaning
	Root tag
	Level Component Tag; no data content
	Component Tag; no data content



Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02
Common Global Implementation (CGI)
BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

CHANGE LOG:

Version	Date	Change
1.0	04-03-2013	Document created
2.0	20-12-2013	Version 2

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
		BkToCstmrDbtCdtNtfctn							
1.0	Group Header	GrpHdr	[1..1]	Component	Set of characteristics shared by all individual transactions included in the message.	R/M			
1.1	MessageIdentification	+MsgId	[1..1]	Max35Text	Point to point reference assigned by the instructing party and sent to the next party in the chain to unambiguously identify the message.	R/M			Unique reference: Concatenation of technical key of 12 characters and sequence number of 9 characters.
1.2	CreationDateTime	+CreDtTm	[1..1]	isoDateTime	Date and time at which the message was created by the account servicer.	R/M	Date and time at which the message was created		Time of creation
2.0	Notification	Ntfctn	[1..n]	Component	Notifies debit and credit entries for the account	R/M			
2.1	Identification	+Id	[1..1]	Max35Text	Unique and unambiguous identification of the account report, assigned by the account servicer.	R/M	Unique per notification and account		Unique reference: Technical key of 12 characters
2.2	ElectronicSequenceNumber	+ElctrncSeqNb	[0..1]	Number 18	Sequential number of the report, assigned by the account servicer. It is increased incrementally for each report sent electronically.	R/M	Sequential number of the report, assigned by the account servicer. It is increased incrementally by 1 for each report sent electronically		Electronic statement number, starts from number one when service established.
2.3	LegalSequenceNumber	+LglSeqNb	[0..1]	Number 18	Legal sequential number of the report, assigned by the account servicer. It is increased incrementally for each report sent.	R/M	Legal sequential number of the report, assigned by the account servicer		Set to 0 when no postings present
2.4	CreationDateTime	+CreDtTm	[1..1]	isoDateTime	Date and time at which the report was created.	R/M	Date and time at which the report was created		Current date and time in isoDateTime format

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.5	FromDate	+FrToDt	[1..1]	Component	Range of time between the start date and the end date for which the account report is issued.	R/M	Range of time between the start date and the end date for which the account report is issued		
5.1.0	FromDateTime	++FrDtTm	[1..1]	IsoDateTime	Date and time at which the range starts.	R/M			
5.1.1	ToDateTime	++ToDtTm	[1..1]	IsoDateTime	Date and time at which the range ends.	R/M			
2.10	Account	+Acct	[1..1]	Component	Unambiguous identification of the account to which credit and debit entries are made.	R/M			
1.2.0	Identification	++Id	[1..1]	Account identification component	Unique and unambiguous identification of the account between the account owner and the account servicer.	R/M	Either <IBAN> or <Othr> must be populated		Always IBAN
1.2.1	IBAN	+++IBAN	[1..1]	IBANIdentifier	International Bank Account Number (IBAN) identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services -International Bank Account Number (IBAN)" version 1997- 10-01, or later revisions.	R/M			Account owners IBAN account number
1.2.11	Currency	++Ccy	[0..1]	Currency Code	Identification of the currency in which the account is held.	R/M			Currency of account

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
1.2.12	Name	++Nm	[0..1]	Max140text	Name of the account, assigned by the account servicing institution in agreement with the account owner in order to provide an additional means of identification of the account.	R/M			Bank Account name and possible name given by the customer to the account if present.
1.2.13	Owner	++Ownr	[0..1]	Party Identification Component	Party that legally owns the account.	R/M			
1.2.14	Name	+++Nm	[0..1]	Max140Text	Name by which a party is known and which is usually used to identify that party.	R/M			Account owner name
1.2.15	PostalAddress	+++PstlAdr	[0..1]	Component	Information that locates and identifies a specific address, as defined by postal services.	R/M			
1.2.19	StreetName	++++StrtNm	[0..1]	Max70Text	Name of a street or thoroughfare.	R/M			Account owners address
1.2.20	BuildingNumber	++++BldgNb	[0..1]	Max16Text	Number that identifies the position of a building on a street.	R/M			Account owners address
1.2.21	PostCode	++++PstCd	[0..1]	Max16Text	Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.	R/M			Account owners address
1.2.22	TownName	++++TwnNm	[0..1]	Max35Text	Name of a built-up area, with defined boundaries, and a local government.	R/M			Account owners address
1.2.23	CountrySubDivision	++++CtrySubDvsn	[0..1]	Country Code	Identifies a subdivision of a country eg, state, region, country.	R/M			
1.2.24	Country	++++Ctry	[0..1]	Country Code	Nation with its own government.	R/M			Account owners country code

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
1.2.26	Identification	+++Id	[0..1]	Account Identification Component	Unique and unambiguous identification of the account between the account owner and the account servicer.	R/M			
1.2.27	Organization Identification	++++OrdIg	[0..1]	Component	Unique and unambiguous way of identifying an organization.	C			
1.2.29	Other	+++++Othr	[0..n]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C	Bank specific id for the customer		
1.2.30	Identification	+++++Id	[1..1]	Max35Text	Identification assigned by an institution.	R/M			Contains external customer number
1.2.31	SchemeName	+++++SchmeNm	[0..1]	Choice Component	Name of the identification scheme.	C			
1.2.32	Code	+++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			Always filled with "CUST"
1.2.56	Servicer	++Svcr	[0..1]	Financial Institution Identification Component	Party that manages the account on behalf of the account owner, ie, manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.	R/M	Provide at minimum at least BIC, Clearing System Member Id or Other Id in this priority order		

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
1.2.57	FinancialInstitutionIdentification	+++FinInstnId	{1..1}	Component	Unique and unambiguous identifier of a financial institution, as assigned under an internationally recognized or proprietary identification scheme.	R/M			
1.2.58	BIC	++++BIC	{0..1}	Code	Bank Identifier Code. Code allocated to financial institutions by the Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).	R/M			BIC code according to country
2.23	TransactionsSummary	+TxSummary	{0..1}	Component	Set of elements used to provide summary information on entries.	C	If used, Total Credit and/or Total Debit should, at a minimum, be provided if summary data is available		Component used if entries exist in the message
2.24	TotalEntries	++TtlNtries	{0..1}	Component	Specifies the total number and sum of debit and credit entries.	R/M			
2.25	NumberOfEntries	+++NbOfNtries	{0..1}	Max15NumericText	Number of individual entries included in the report.	R/M			Calculated number of entries in the file.
2.26	Sum	+++Sum	{0..1}	Decimal	Total of all individual entries included in the report.	R/M	Either Number of Entries or Sum or both of them should be reported		Calculated sum of included entries in the file
2.27	TotalNetEntryAmount	+++TtlNetNtryAmt	{0..1}	Decimal	Resulting amount of the netted amounts for all debit and credit entries.	R/M			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.28	CreditDebitIndicator	+++CdtDbtInd	[0..1]	Code	Indicates whether the total net entry amount is a credit or a debit amount.	R/M			Following values are valid: DBIT = Debit CRDT = Credit
2.29	TotalCreditEntries	++TtlCdtNtries	[0..1]	Component	Specifies the total number and sum of credit entries.	R/M			
2.30	NumberOfEntries	+++NbOfNtries	[0..1]	Max15NumericText	Number of individual entries included in the report.	R/M	Either Number of Entries or Sum or both of them should be reported		Calculated number of credit entries in the file.
2.31	Sum	+++Sum	[0..1]	DecimalNumber	Total of all individual entries included in the report.	R/M	Either Number of Entries or Sum or both of them should be reported		Calculated sum of included credit entries in the file
2.32	TotalDebitEntries	++TtlDbtNtries	[0..1]	Component	Total of all individual entries included in the report.	R/M			
2.33	NumberOfEntries	+++NbOfNtries	[0..1]	Max15NumericText	Number of individual entries included in the report.	R/M	Either Number of Entries or Sum or both of them should be reported		Calculated number of debit entries in the file.
2.34	Sum	+++Sum	[0..1]	DecimalNumber	Total of all individual entries included in the report.	R/M	Either Number of Entries or Sum or both of them should be reported		Calculated sum of included debit entries in the file
2.56	Entry	+Ntry	[0..n]	Component	Specifies the elements of an entry in the report.	R/M	Can be absent if no movement for the account. For reporting single transaction or batch or collection of batches		
2.57	EntryReference	++NtryRef	[0..1]	Max35Text	Unique reference for the entry.	R/M	Unique per transaction within one notification		Calculated within message starting from 1
2.58	Amount	++Amt	[1..1]	Currency and Amount	Amount of money in the cash entry.	R/M	Amount in the currency of the account reported. Note: This amount can be Zero		Amount of transaction
2.59	CreditDebitIndicator	++CdtDbtInd	[1..1]	Code	Specifies if an entry is a credit or a debit.	R/M	Treat as credit for Zero amount, unless the coding scheme treats it otherwise e.g. BAI may also designate it as a debit		Following values can be used DBIT = Debit CRDT = Credit
2.60	ReversalIndicator	++RvsInd	[0..1]	Indicator	Indicates whether the entry is the result of a reversal operation.	R/M	Value is TRUE or FALSE. Should only be shown if TRUE		Only shown when value = TRUE, otherwise the tag is not present

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.61	Status	++Sts	[1..1]	Code	Status of an entry on the books of the account servicer.	R/M	BOOK = Booked PDNG = Pending INFO = Information	INFO only used for failed direct debits in Finland	Only BOOK and INFO are used by Danske Bank Group
2.62	BookingDate	++BookgDt	[0..1]	Component	Date and time when an entry is posted to an account on the account servicer's books.	R/M			
4.1.0	Date	++Dt	[0..1]	ISO Date	Specified Date	C			Booking date of the transaction
2.63	ValueDate	++ValDt	[0..1]	Component	Date and time assets become available the account owner (in a debit entry).	R/M	Only Use Date		
4.1.0	Date	++Dt	[0..1]	ISO Date	Specified Date	C			Value date of the transaction
2.64	AccountServicer Reference	++AcctSvcrRef	[0..1]	Max35Text	Account servicing institution's reference for the entry.	R/M	When the same booked entry is reported in both the camt.052 or camt.054, the Account Service reference should be the same as reported in camt.053	Contains filing code for Finland when not a bulk posting	Unique ref. for the transaction. CGI rules apply meaning that the same transaction will have the same reference when reported in camt.052, camt.053 and camt.054
2.71	BankTransactionCode	++BkTxCd	[1..1]	Component	Set of elements to fully identify the type of underlying transaction resulting in an entry.	R/M	Domain and/or proprietary may be provided. At least one must be provided		Please refer to the Bank Transaction code appendix for a list of used codes
2.72	Domain	+++Domn	[0..1]	Component	Specifies the domain, the family and the sub-family of the bank transaction code, in a structured and hierarchical format.	R/M	Standard BTC are used as first priority. For INFO status coded entries ACMT/MCOP/NTAV is used		
2.73	Code	++++Cd	[1..1]	ExternalBankTransactionDomainCode	Specifies the business area of the underlying transaction.	R/M			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.74	Family	++++Fmly	[1..1]	Component	Specifies the family and the sub-family of the bank transaction code, within a specific domain, in a structured and hierarchical format.	R/M			
2.75	Code	+++++Cd	[1..1]	ExternalBankTransactionFamilyCode	Specifies the family within a domain.	R/M		For Finland: Domain family code from list YAS0001 Z	Domain family code according to entry def. code
2.76	SubFamilyCode	+++++SubFmlyCd	[1..1]	ExternalBankTransactionSubFamilyCode	Specifies the sub-product family within a specific family.	R/M		For Finland: Domain sub family code from list YAS0001 Z	Domain sub family code according to entry def. code
2.77	Proprietary	+++Prtry	[1..1]	Component	Proprietary identification of the bank transaction code, as defined by the issuer.	R/M	For bank or community specific transaction coding		
2.78	Code	++++Cd	[1..1]	Max35Text	Proprietary bank transaction code to identify the underlying transaction.	R/M	Code format is depending on the issuer. It may be a composite code	For Finland, contains the Entry def. code specified by FFFS	Contains the account entry text of the transaction

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.79	Issuer	++++Issr	[0..1]	Max35Text	Identification of the issuer of the proprietary bank transaction code	R/M	Value samples (not exhausted): BAI = BAI Code SWIFT = Swift Code BBA = Belgian Code CFONB = French Code FFFS = Finnish Code ZKA = German Code GVC = German Code AEB = Spanish Code DBA = Danish Code Also other values available such as bank name	Always value 'FFFS' in Finland and 'DBA' in Denmark	Only used for Danish and Finnish accounts
2.81	AdditionalInformationIndicator	++AddtlInflnd	[0..1]	Component		R/M			
2.82	MessageNameIdentification	+++MsgNmld	[0..1]	Max35Text	Specifies the message name identifier of the message that is used to provide additional details.	C			Danske Bank reference
2.115	EntryDetails	++NtryDtls	[0..n]	Component	Set of elements used to provide details on the entry.	C	This provides a breakdown of the transaction details when the entry is 'batched'. If the entry is not batched and transaction details are to be reported, then transaction details must only occur once		
2.116	Batch	+++Btch	[0..1]	Component	Set of elements used to provide details on batched transactions.	C			Component only present when reporting on batched transactions.
2.117	MessageIdentification	++++Msgld	[0..1]	Max35Text	Point to point reference, as assigned by the sending party, to unambiguously identify the batch of transactions.	C			Contains the message id from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. In other cases the value is blank

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.118	PaymentInformationIdentification	++++PmtInflId	[0..1]	Max35Text	Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.	C			Contains the payment information id from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. In other cases the value is blank
2.119	NumberOfTransactions	++++NbOfTx	[0..1]	Max15NumericText	Number of individual transactions included in the batch.	C			
2.120	TotalAmount	++++TtIAmt	[0..1]	CurrencyAndAmount	Total amount of money reported in the batch entry.	C			Currency set as xml attribute.
2.121	CreditDebitIndicator	++++CdtDbtInd	[0..1]		Set of elements providing information on the underlying transaction(s).	C	Indicate a Debit or Credit , if Total Amount is provided		Filled if TtIAmt is filled.
2.122	TransactionDetails	+++TxDtIs	[0..n]	Component	Set of elements providing information on the underlying transaction(s).	R/M			
2.123	References	++++Refs	[0..1]	Component	Set of elements providing the identification of the underlying transaction	C			
2.125	AccountServicerReference	+++++AcctSvcrRef	[0..1]	Max35Text	The account servicing institution's reference for the transaction.	C	The account servicing institution's reference for the transaction	In Finland the field contains a filing code.	Unique reference for the transaction.

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.127	InstructionIdentification	+++++InstrId	[0..1]	Max35Text	Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.	C			In other countries than Finland the field contains the instruction ID from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. In other cases the value is blank
2.128	EndToEndIdentification	+++++EndToEndId	[0..1]	Max35Text	Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.	C	The end-to-end identification must be reported when it is known by the reporting bank. For SEPA the EndToEndId can be 'NOTPROVIDED'		Available EndToEndId from the incoming SEPA transaction. If not provided the value will be "NOTPROVIDED" The EndToEndId will also be present if the transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. In other cases the value is blank
2.129	TransactionIdentification	+++++TxId	[0..1]	Max35Text	Unique identification assigned by the first instructing agent to unambiguously identify the transaction and passed on, unchanged, throughout the entire interbank chain.	C			Contains the Transaction Id from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. . . In other cases the value is blank

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.130	MandateIdentification	+++++MndtId	[0..1]	Max35Text	Reference of the direct debit mandate that has been signed between by the debtor and the creditor.	C	For reporting Direct Debits, as appropriate		Contains the mandate Id on both credit and debit transactions related to Sepa Direct Debit
2.133	Proprietary	+++++Prtry	[0..1]	Component	Proprietary reference of an underlying transaction.	C			
2.134	Type	+++++Tp	[1..1]	Max35Text	Identifies the type of reference reported.	C			CARD for card transactions or ORIG for return payments
2.135	Reference	+++++Ref	[1..1]	Max35Text	Proprietary reference specification related to the underlying transaction.	C			The card number used in the credit transaction is provided if available.
2.136	AmountDetails	+++++AmtDtls	[0..1]	Component	Set of elements providing details information on the original amount	R/M	All Amount Details are in all cases given on the Transaction Details level on single and batch bookings. For consistency purposes Entry/Amount information is repeated at TransactionDetails/AmountDetails/TransactionAmount		

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.1.0	InstructedAmount	+++++InstdAmt	[0..1]	Component	Identifies the amount of money to be moved between the debtor and creditor, before deduction expressed in the currency as ordered by the initiating party and provides currency exchange info instructed amount and/or currency is/are different from the entry amount and/or currency.	C	Used for original amount in original currency and is the gross value (i.e. prior to application of charges) in same currency situations. For example in the inter-bank MT103 message this amount reports the 33B field contents. Instructed Amount may be omitted in the case when there are no charges or no FX. In FX cases the booked transaction FX information can be found with Transaction Amount. When account servicing bank is receiving a transaction via MT103, it might contain other FX information of sender bank FX operation. This is only in the situation of original payment initiation done with Equivalent amount		
2.1.1	Amount	+++++Amt	[0..1]	CurrencyAndAmount	Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.	C	Used for original amount in original currency and is the gross value (i.e. prior to application of charges) in same currency situations		
2.1.9	TransactionAmount	+++++TxAmt	[0..1]	Component	Amount of the underlying transaction.	C	EPC Mandated for SEPA payments		
2.1.10	Amount	+++++Amt	[0..1]	Amount	Amount of money to be moved between the debtor the currency as ordered by the initiating party.	C			Amount in account currency. Is present always both in single and itemization transactions.
2.1.11	CurrencyExchange	+++++CcyXchg	[0..1]	Component	Reports on currency exchange information	C	For reporting FX transaction details		

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.1.12	SourceCurrency	+++++++SrcCcy	[0..1]	CurrencyCode	Currency of the amount to be converted in a currency conversion.	C	Original amount currency of the currency exchange made		
2.1.13	TargetCurrency	+++++++TrgtCcy	[0..1]	CurrencyCode	Currency into which an amount is to be converted in a currency conversion.	C	Resulting currency of the currency exchange made. Reported if available		
2.1.14	UnitCurrency	+++++++UnitCcy	[0..1]	CurrencyCode	Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.	C	Define in which direction the exchange rate is calculated. Reported if available. Decided by the reporting bank or community practice		
2.1.15	ExchangeRate	+++++++XchgRate	[0..1]	BaseOneRate	Factor used for the conversion of an amount from one currency into another. This reflects the price at which one currency was bought with another currency.	C	Given in direction of UnitCurrency and Quotation Currency like "EUR/USD exchange rate is 1.3 (USD per EUR), the price currency is USD and the unit currency is EUR"		
2.1.36	ProprietaryAmount	+++++PrtryAmt	[0..n]	Component	Provides proprietary amount information	C	This value can be used by the bank for additional amount reporting on community or bank-specific purposes		
2.1.37	Type	+++++Tp	[1..1]	Max35Text	Identifies the type of amount.	C			
2.1.38	Amount	+++++Amt	[1..1]	CurrencyAndAmount	Identifies the proprietary amount.	C			
2.1.39	CurrencyExchange	+++++CcyXchg	[0..1]	Component	Reports on currency exchange information.	C	For reporting FX transaction details		
2.1.40	SourceCurrency	+++++++SrcCcy	[0..1]	CurrencyCode	Currency of the amount to be converted in a currency conversion.	C	Original amount currency of the currency exchange made		
2.1.41	TargetCurrency	+++++++TrgtCcy	[0..1]	CurrencyCode	Currency into which an amount is to be converted in a currency conversion.	C	Resulting currency of the currency exchange made. Reported if available		

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.1.42	UnitCurrency	+++++++UnitC cy	[0..1]	CurrencyCode	Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.	C	Define in which direction the exchange rate is calculated. Reported if available. Decided by the reporting bank or community practice		
2.1.43	ExchangeRate	+++++++XchgR ate	[0..1]	BaseOneRate	Factor used for the conversion of an amount from one currency into another. This reflects the price at which one currency was bought with another currency.	C			
2.143	BankTransactio nsCode	++++BkTxCd	[0..1]	Component	Set of elements to fully identify the type of underlying transaction resulting in an entry.	R/M	Further qualification of the entry level bank transaction code. Bank Transaction Code must be provided at entry level and maybe provided at transaction detail level. Note: Domain and/or proprietary may be provided. At least one must be provided		
2.144	Domain	+++++Domn	[0..1]	Component	Specifies the domain, the family and the sub-family of the bank transaction code, in a structured and hierarchical format.	R/M	Recommendation suggested that standard BTC are used as first priority. For INFO status coded entries ACMT/MCOP/NTAV is used		Please refer to the Bank Transaction code appendix for a list of used codes
2.145	Code	+++++Cd	[1..1]	ExternalBankT ransactionDo mainCode	Specifies the business area of the underlying transaction.	R/M			
2.146	Family	+++++Fmly	[1..1]	Component	Specifies the family and the sub-family of the bank transaction code, within a specific domain, in a structured and hierarchical format.	R/M			
2.147	Code	+++++++Cd	[1..1]	ExternalBankT ransactionFa milyCode	Specifies the family within a domain.	R/M			
2.148	SubfamilyCode	+++++++SubF mlyCd	[1..1]	ExternalBankT ransactionSub FamilyCode	Specifies the sub-product family within a specific family.	R/M			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.149	Proprietary	+++++Prtry	[0..1]	Component	Proprietary identification of the bank transaction code, as defined by the issuer.	R/M	For bank or community specific transaction coding		
2.150	Code	+++++Cd	[1..1]	Max35Text	Proprietary bank transaction code to identify the underlying transaction.	R/M	Code format is depending on the issuer. It may be a composite code	For Finland, contains the Entry def. code specified by FFFS	Contains the account entry text of the transaction
2.151	Issuer	+++++Issr	[0..1]	Max35Text	Identification of the issuer of the proprietary bank transaction code.	R/M	Value samples (not exhausted): BAI = BAI Code SWIFT = Swift Code BBA = Belgian Code CFONB = French Code FFFS = Finnish Code ZKA = German Code GVC = German Code AEB = Spanish Code DBA = Danish Code Also other values available such as bank name	Always value 'FFFS' in Finland and 'DBA' in Denmark	Only used for Danish and Finnish accounts
2.179	RelatedParties	++++RltdPties	[0..1]	Component	Set of elements identifying the parties related to the underlying transaction.	C			
2.181	Debtor	+++++Dbtr	[0..1]	Party Identification Component	Party that owes an amount of money to the (ultimate) creditor.	C	For outward payments, report if different from account owner. For inward payments, report where available. In instances where the ReversalIndicator <RvslInd> is TRUE, the Creditor and Debtor must be the same as the Creditor and Debtor of the original entry. EPC mandated for SEPA Payment - For SEPA inward payments, it is expected that the Debtor info would be provided by the Debtor Agent and hence would be reported		Present in case of a credit transaction

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
9.1.0	Name	+++++Nm	[0..1]	Max70Text	Name of the debtor.	C			In case of a credit transaction the field contains the debtor name from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. In other cases the value is blank
9.1.1	PostalAddress	+++++PstAdr	[0..1]	Component	Information that locates and identifies a specific address, as defined by postal services.	C			Contains the primary address of the Debtor if available
9.1.5	StreetName	+++++StrtNm	[0..1]	Max70Text	Name of a street or thoroughfare	C			
9.1.6	BuildingName	+++++BldgNb	[0..1]	Max16Text	Number that identifies the position of a building on a street.	C			
9.1.7	Postal Code	+++++PstCd	[0..1]	Max16Text	Identifies the nature of the postal address.	C			
9.1.8	Town Name	+++++TwnNm	[0..1]	Max35Text	Name of a built-up area, with defined boundaries, and a local government.	C			
9.1.10	Country	+++++Ctry	[0..1]	CountryCode	Nation with its own government.	C			
9.1.11	AddressLine	+++++AdrLine	[0..1]	Max70Text	Information that locates and identifies a specific address, as defined by postal services, that is presented in free format text.	C			
9.1.12	Identification	+++++Id	[0..1]	ChoiceComponent	Unique and unambiguous way of identifying an organization or an individual person.	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
9.1.13	OrganizationIdentification	+++++++OrgId	[1..1]	Component	Unique and unambiguous way of identifying an organization.	C			
9.1.14	BICOrBEI	+++++++BICOrBEI	[0..1]	Identifier	Code allocated to organizations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).	C			
9.1.15	Other	+++++++Othr	[0..n]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
9.1.16	Identification	+++++++Id	[1..1]	Max35Text	Identification assigned by an institution.	C			
9.1.17	SchemeName	+++++++SchemeNm	[0..1]	Component	Name of the identification scheme.	C			
9.1.18	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
9.1.19	Proprietary	+++++++Prttry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			
9.1.20	Issuer	+++++++Issr	[0..1]	Max35Text	Entity that assigns the identification.	C			
1.2.35	PrivateIdentification	+++++++PrvtId	[1..1]	Component	Unique and unambiguous identification of a party	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
1.2.36	DateAndPlaceOf Birth	+++++++DtAndPlcOfBirth	[0..1]	Component	Date and place of birth of a person	C			
1.2.37	BirthDate	+++++++BirthDt	[1..1]	ISOdate	Date on which a person is born	C			
1.2.38	ProvinceOfBirth	+++++++PrcOfBirth	[0..1]	Max35Text	Province where a person was born	C			
1.2.39	CityOfBirth	+++++++CityOfBirth	[1..1]	Max35Text	City where a person was born	C			
1.2.40	CountryOfBirth	+++++++CtryOfBirth	[1..1]	CountryCode	Country where a person was born	C			
1.2.41	Other	+++++++Other	[0..1]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
1.2.42	Identification	+++++++Id	[1..1]	Max35Text	Unique and unambiguous identification of a person	C			
1.2.43	SchemeName	+++++++SchemeNm	[0..1]	ChoiceComponent	Name of the identification scheme.	C			
1.2.44	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
1.2.45	Proprietary	+++++++Prtry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			
1.2.46	Issuer	+++++++Issuer	[0..1]	Max35Text	Entity that assigns the identification	C			
1.2.47	CountryOfResidence	+++++++CtryOfRes	[0..1]	Country Code	Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.182	DebtorAccount	+++++DbtrAcct	{0..1}	Component	Unambiguous identification of the account of the debtor.	C	For inward payment, Report where available. Conditional on the country regulatory requirement		
1.1.0	Identification	+++++Id	{0..1}	Account Identification Component	Unique and unambiguous identification of the account between the account owner and the account servicer.	C			
1.1.1	IBAN Account number	+++++++Iban	{0..1}	IBANIdentifier	International Bank Account Number (IBAN) identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services -International Bank Account Number (IBAN)" version 1997- 10-01, or later revisions.	C		Finland only: Only used in a cash pool setup. Counter account will be shown for credit entries	In case of a credit transaction the field contains the debtor account from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. In other cases the value is blank
2.183	UltimateDebtor	+++++UltmtDbtr	{0..1}	Party Identification Component	Ultimate party that owes an amount of money to the {ultimate} creditor.	C	Ultimate party that owes an amount of money to the {ultimate} creditor		

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
9.1.0	Name	+++++Nm	[0..1]	Max140Text	Name of the account, assigned by the account servicing institution in agreement with the account owner in order to provide an additional means of identification of the account.	C		(U-turns apply to Finland only)	In case of a credit transaction the field contains the Ultimate Debtor name from the incoming SEPA transaction or if transaction is created via ISO 20022 XML pain 001 Customer Credit Transfer in Danske Bank. The tag is also filled if reporting on a finnish u-turn transactions. In other cases the value is blank
9.1.1	PostalAddress	+++++PstlAdr	[0..1]	Component	Information that locates and identifies a specific address, as defined by postal services.	C			
9.1.5	StreetName	++++++StrtNm	[0..1]	Max70Text	Name of a street or thoroughfare.	C			
9.1.6	BuildingNumber	++++++BldgNb	[0..1]	Max16Text	Number that identifies the position of a building on a street.	C			
9.1.7	PostCode	++++++PstCd	[0..1]	Max16Text	Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.	C			
9.1.8	TownName	++++++TwnNm	[0..1]	Max35Text	Name of a built-up area, with defined boundaries, and a local government.				
9.1.10	Country	++++++Ctry	[0..1]	CountryCode	Nation with its own government.	C			
9.1.11	AddressLine	++++++AdrLine	[0..1]	Max70Text	Information that locates and identifies a specific	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					address, as defined by postal services, that is presented in free format text.				
9.1.12	Identification	+++++Id	[0..1]	ChoiceComponent	Unique and unambiguous way of identifying an organization or an individual person.	C			
9.1.13	OrganizationIdentification	+++++OrgId	[1..1]	Component	Unique and unambiguous way of identifying an organization.	C			
9.1.14	BICOrBEI	+++++BICOrBEI	[0..1]	Identifier	Code allocated to organizations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).	C			
9.1.15	Other	+++++Othr	[0..n]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
9.1.16	Identification	+++++Id	[1..1]	Max35Text	Identification assigned by an institution.	C			
9.1.17	SchemeName	+++++SchemeNm	[0..1]	Component	Name of the identification scheme.	C			
9.1.18	Code	+++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					published in an external list.				
9.1.19	Proprietary	+++++++P rtry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			
9.1.20	Issuer	+++++++Iss r	[0..1]	Max35Text	Entity that assigns the identification.	C			
1.2.35	Private Identification	+++++++Prvtl d	[1..1]	Component	Unique and unambiguous identification of a party	C			
1.2.36	DateAndPlaceOf Birth	+++++++Dt AndPlcOfBirth	[0..1]	Component	Date and place of birth of a person	C			
1.2.37	BirthDate	+++++++Bi rthDt	[1..1]	ISOdate	Date on which a person is born	C			
1.2.38	ProvinceOfBirth	+++++++P rvcOfBirth	[0..1]	Max35Text	Province where a person was born	C			
1.2.39	CityOfBirth	+++++++Ci tyOfBirth	[1..1]	Max35Text	City where a person was born	C			
1.2.40	CountryOfBirth	+++++++C tryOfBirth	[1..1]	CountryCode	Country where a person was born	C			
1.2.41	Other	+++++++Oth r	[0..1]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
1.2.42	Identification	+++++++Id	[1..1]	Max35Text	Unique and unambiguous identification of a person	C			
1.2.43	SchemeName	+++++++S chmeNm	[0..1]	ChoiceCompo nent	Name of the identification scheme.	C			
1.2.44	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
1.2.45	Proprietary	+++++++Prtry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
1.2.46	Issuer	+++++++Issuer	[0..1]	Max35Text	Entity that assigns the identification	C			
1.2.47	CountryOf Residence	+++++++CtryOf Res	[0..1]	Country Code	Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.	C			
2.184	Creditor	+++++Cdtr	[0..1]	Party Identification Component	Party to which an amount of money is due.	C	For outward payment, report where available		
9.1.0	Name	+++++Nm	[0..1]	Text	Name of the account, assigned by the account servicing institution in agreement with the account owner in order to provide an additional means of identification of the account.	C			In case of a debit transaction the field contains the creditor name from the SEPA transaction or if transaction is created via ISO 20022 XML pain 001 in Danske Bank. In other cases the value is blank.
9.1.1	PostalAddress	+++++PstAdr	[0..1]	Component	Information that locates and identifies a specific address, as defined by postal services.	C			
9.1.7	PostCode	+++++PstCd	[0..1]	Max16Text	Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.	C			
9.1.8	TownName	+++++TwnNm	[0..1]	Max35Text	Name of a built-up area, with defined boundaries, and a local government.	C			
9.1.10	Country	+++++Ctry	[0..1]	CountryCode	Nation with its own government.	C			
9.1.11	AddressLine	+++++AdrLine	[0..2]	Max70Text	Information that locates and identifies a specific address, as defined by	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					postal services, that is presented in free format text.				
9.1.12	Identification	+++++Id	[1..1]	ChoiceComponent	Unique and unambiguous way of identifying an organization or an individual person.	C			
9.1.13	OrganizationIdentification	++++++OrgId	[0..1]	Component	Unique an unambiguous way of identifying an organization.	C			
9.1.14	BICOrBEI	++++++BICOrBEI	[0..n]	Identifier	Code allocated to organizations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).	C			
9.1.15	Other	++++++Othr	[1..n]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
9.1.16	Identification	++++++Id	[1..1]	Max35Text	Identification assigned by an institution.	C			
9.1.17	SchemeName	++++++SchemeNm	[0..1]	ChoiceComponent	Name of the identification scheme.	C			
9.1.18	Code	++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
9.1.19	Proprietary	++++++Ptry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
9.1.20	Issuer	+++++++Issr	[0..1]	Max35Text	Entity that assigns the identification.	C			
9.1.21	PrivateIdentification	+++++++PrvtId	[1..1]	Component	Unique and unambiguous identification of a party	C			
9.1.22	DateAndPlaceOfBirth	+++++++DtAndPlcOfBirth	[0..1]	Component	Date and place of birth of a person	C			
9.1.23	BirthDate	+++++++BirthDt	[1..1]	ISOdate	Date on which a person is born	C			
9.1.24	ProvinceOfBirth	+++++++PrcvOfBirth	[0..1]	Max35Text	Province where a person was born	C			
9.1.25	CityOfBirth	+++++++CityOfBirth	[1..1]	Max35Text	City where a person was born	C			
9.1.26	CountryOfBirth	+++++++CtryOfBirth	[1..1]	CountryCode	Country where a person was born	C			
9.1.27	Other	+++++++Other	[0..1]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
9.1.28	Identification	+++++++Id	[1..1]	Max35Text	Unique and unambiguous identification of a person	C			
9.1.29	SchemeName	+++++++SchemeNm	[0..1]	ChoiceComponent	Name of the identification scheme.	C			
9.1.30	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
9.1.31	Proprietary	+++++++Prtry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			
9.1.32	Issuer	+++++++Issr	[0..1]	Max35Text	Entity that assigns the identification	C			
9.1.33	CountryOfResidence	+++++++CtryOfRes	[0..1]	Country Code	Country in which a person resides (the place of a person's	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					home). In the case of a company, it is the country from which the affairs of that company are directed.				
2.185	CreditorAccount	+++++CdtrAcct	[0..1]	Component		C	For outward, payment, Report where available		
1.1.0	Identification	+++++Id	[0..1]	Identifier	Unique and unambiguous identification of the account between the account owner and the account servicer.	C			
1.1.1	IBAN Account number	++++++Iban	[0..1]	IBANIdentifier	International Bank Account Number (IBAN) identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services -International Bank Account Number (IBAN)" version 1997- 10-01, or later revisions.	C			Contains the counter account when available.
1.1.2	Other	++++++Othr	[0..1]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
1.1.3	Identification	++++++Id	[1..1]	Max35Text	Unique and unambiguous identification of a person	C			
1.1.4	SchemeName	++++++SchmeNm	[0..1]	ChoiceComponent	Name of the identification scheme.	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
1.1.5	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
1.1.6	Proprietary	+++++++Prt ry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			
1.1.8	Type	+++++Tp	[0..1]	Component	Nature, or use of the account	C			
2.186	UltimateCreditor	+++++UltmtCdt r	[0..1]	Party Identifier Component	Ultimate party to which an amount of money is due	C	Ultimate party to which an amount of money is due		
9.1.0	Name	+++++Nm	[0..1]	Max140Text	Name of the account, assigned by the account servicing institution in agreement with the account owner in order to provide an additional means of identification of the account.	C			In case of a debit transaction the field contains the creditor name from the SEPA transaction or if transaction is created via ISO 20022 XML pain 001 in Danske Bank. In other cases the value is blank.
9.1.1	PostalAddress	+++++PstAdr	[0..1]	Component	Information that locates and identifies a specific address, as defined by postal services.	C			
9.1.7	PostCode	+++++PstCd	[0..1]	Max16Text	Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.	C			
9.1.8	TownName	+++++TwnNm	[0..1]	Max35Text	Name of a built-up area, with defined boundaries, and a local government.	C			
9.1.10	Country	+++++Ctry	[0..1]	CountryCode	Nation with its own government.	C			
9.1.11	AddressLine	+++++AdrLine	[0..2]	Max70Text	Information that locates and identifies a specific address, as defined by	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					postal services, that is presented in free format text.				
9.1.12	Identification	+++++Id	[1..1]	ChoiceComponent	Unique and unambiguous way of identifying an organization or an individual person.	C			
9.1.13	Organization Identification	++++++OrgId	[0..1]	Component	Unique an unambiguous way of identifying an organization.	C			
9.1.14	BICOrBEI	++++++BICOrBEI	[0..n]	Identifier	Code allocated to organizations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).	C			
9.1.15	Other	+++++++Othr	[0..n]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
9.1.16	Identification	+++++++Id	[1..1]	Max35Text	Identification assigned by an institution.	C			
9.1.17	SchemeName	+++++++SchemeNm	[0..1]	ChoiceComponent	Name of the identification scheme.	C			
9.1.18	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
9.1.19	Proprietary	+++++++Ptry	[1..1]	Max35Text	Name of the identification scheme, in a free text form.	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
9.1.20	Issuer	+++++++Issr	[0..1]	Max35Text	Entity that assigns the identification.	C			
9.1.21	Private Identification	+++++++PrvtId	[1..1]	Component	Unique and unambiguous identification of a party	C			
9.1.22	DateAndPlaceOf Birth	+++++++DtAndPlcOfBirth	[0..1]	Component	Date and place of birth of a person	C			
9.1.23	BirthDate	+++++++BirthDt	[1..1]	ISOdate	Date on which a person is born	C			
9.1.24	ProvinceOfBirth	+++++++PrvcOfBirth	[0..1]	Max35Text	Province where a person was born	C			
9.1.25	CityOfBirth	+++++++CityOfBirth	[1..1]	Max35Text	City where a person was born	C			
9.1.26	CountryOfBirth	+++++++CountryOfBirth	[1..1]	CountryCode	Country where a person was born	C			
9.1.27	Other	+++++++Othr	[0..1]	Component	Unique identification of an organization, as assigned by an institution, using an identification scheme.	C			
9.1.28	Identification	+++++++Id	[1..1]	Max35Text	Unique and unambiguous 5.1.6415.1.641 identification of a person	C			
9.1.29	SchemeName	+++++++SchemeNm	[0..1]	ChoiceComponent	Name of the identification scheme.	C			
9.1.30	Code	+++++++Cd	[1..1]	Code	Name of the identification scheme, in a coded form as published in an external list.	C			
9.1.31	Proprietary	+++++++Proprietary	[1..1]	Max35Text	Name of the identification scheme, in a freetext form.	C			
9.1.32	Issuer	+++++++Issr	[0..1]	Max35Text	Entity that assigns the identification	C			
9.1.33	CountryOfResidence	+++++++CountryOfRes	[0..1]	Country Code	Country in which a person resides (the	C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.				
2.191	RelatedAgents	++++RltdAgts	[0..1]	Component	Set of elements identifying the agents related to the underlying transaction.	C			
2.193	CreditorAgent	+++++CdtrAgt	[0..1]	Financial institution Identification component	Financial institution servicing an account for the creditor.	C	EPC Mandated for SEPA CT and DD	When reporting on Finnish accounts only: If Speedup agreement is in effect the BIC is always DABAFIH	
6.1.0	FinancialInstitutionIdentification	++++++FinInstnId	[1..1]	Component	Unique and unambiguous identifier of a financial institution, as assigned under an internationally recognized or proprietary identification scheme	C			
6.1.1	BIC	++++++BIC	[1..1]	BICIdentifier	Bank Identifier Code. Code allocated to financial institutions by the Registration Authority, under an	C		In Finland only: If transaction is marked as	

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					international identification scheme, as described in the latest version of the standard ISO 9362 Banking			a Speedup the BIC is always DABAFIH H	
6.1.2	ClearingSystem MemberIdentification	+++++++ClrSysMmbld	[1..1]	Component	Unique and unambiguous identifier of a clearing system member, as assigned by the system or system administrator.	C			
6.1.6	MemberIdentification	+++++++Mmbld	[1..1]	Max35Text	Identification of a member of a clearing system.	C			
2.204	Purpose	++++Purp	[0..1]	Component	Underlying reason for the payment transaction, eg, a charity payment, or a commercial agreement between the creditor and the debtor.	C	Report when available		
2.205	Code	+++++Cd	[1..1]	ExternalPurposeCode	Specifies the underlying reason for the payment transaction, as published in an external purpose code list.	C			Mapped from the SEPA transaction or if transaction is created via ISO 20022 XML pain 001 in Danske Bank. In other cases the value is blank
2.206	Proprietary	+++++Prtry	[1..1]	Max35Text	User community specific purpose.	C			Mapped from the SEPA transaction or if transaction is created via ISO 20022 XML pain 001 in Danske Bank. In other cases the value is blank
2.214	RemittanceInformation	++++RmtInf	[0..1]	Component	Information that enables the matching, ie, reconciliation, of a payment with the items that the payment is	C	For inward SEPA transaction it is recommended to report, when available		

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					intended to settle, eg, commercial invoices in an account receivable system.				
2.215	Unstructured	+++++Ustrd	[0..n]	Max140Text	Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, eg, commercial invoices in an accounts' receivable system in an unstructured form.	C			Filled with free format Remittance Information received from the payment initiator. The number of Ustrd instances is depended on the transaction type and country specific capabilities.
2.216	Structured	+++++Strd	[0..n]	Component	Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, eg, commercial invoices in an accounts' receivable system in a structured form.	C			Is only present when structured information is available in the transaction.
2.217	ReferredDocumentInformation	+++++RfrdDocInf	[0..n]	Component	Reference information to allow the identification of the underlying reference documents.	C			
2.218	Type	+++++Tp	[0..1]	Component	Provides the type of the referred document.	C			
2.219	CodeOrProprietary	+++++CdOrPrtry	[1..1]	Component	Provides the type details of the referred document.	C			
2.220	Code	+++++Cd	[1..1]	Code	Document type in a coded form.	C			Filled with info from incoming posting. If not XML based posting, this set to CREN or DEBN depending on if it is a credit or debit

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
									transaction.
2.221	Proprietary	+++++++Prt ry	[1..1]	Max35Text	Proprietary identification of the type of the remittance document.	C			Filled with info from incoming posting.
2.222	Issuer	+++++++Issr	[0..1]	Max35Text	Identification of the issuer of the reference document type.	C			Filled with info from incoming posting.
2.223	Number	+++++++Nb	[0..1]	Max35Text	Unique and unambiguous identification of the referred document.	C			Filled with info from incoming posting.
2.224	RelatedDate	+++++++RltdDt	[0..1]	ISODate	Date associated with the referred document.	C			Filled with info from incoming posting.
2.225	ReferredDocu mentAmount	+++++++RfrfDoc Amt	[0..1]	ChoiceCompo nent	Amount of money and currency of a document referred to in the remittance section. The amount is typically either the original amount due and payable, or the amount actually remitted for the referred document.	C			
2.226	DuePayableAmo unt	+++++++DuePy blAmt	[0..1]	CurrencyAndA mount	Amount specified is the exact amount due and payable to the creditor.	C			Filled with info from incoming posting.
2.227	DiscountApplied Amount	+++++++Dscnt ApldAmt	[0..1]	CurrencyAndA mount	Amount of money resulting from the application of an agreed discount to the amount due and payable to the creditor.	C			Filled with info from incoming posting.
2.228	CreditNoteAmo unt	+++++++CdtNo teAmt	[0..1]	CurrencyAndA mount	Amount specified for the referred document is the amount of a credit note.	C			Filled with info from incoming posting.
2.229	TaxAmount	+++++++TaxA mt	[0..1]	CurrencyAndA mount	Quantity of cash resulting from the calculation of the tax.	C			Filled with info from incoming posting.
2.230	AdjustmentAmt AndRsn	+++++++Adjst mntAmtAndRsn	[0..n]	Component		C			

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.231	Amount	+++++++Amt	[0..1]	CurrencyAndAmount	Amount of money of the document adjustment.	C			Filled with info from incoming posting.
2.232	CreditDebitIndicator	+++++++CdtDblnd	[0..1]	Code	Specifies whether the adjustment must be subtracted or added to the total amount.	C			Filled with info from incoming posting.
2.233	Reason	+++++++Rsn	[0..1]	Max4Text	Specifies the reason for the adjustment.	C			Filled with info from incoming posting.
2.234	AdditionalInformation	+++++++Addtlnf	[0..1]	Max140Text	Provides further details on the document adjustment.	C			Filled with info from incoming posting.
2.235	RemittedAmount	+++++++RmtdAmt	[0..1]	CurrencyAndAmount	Amount of money remitted for the referred document.	C			Filled with info from incoming posting.
2.236	CreditorReferenceInformation	+++++++CdtrRefInf	[0..1]	Component	Reference information provided by the creditor to allow the identification of the underlying documents.	C	For remittance creditor reference information, in instances where the CreditorReferenceType Code is SCOR (Structured Communication Reference) and the CreditorReference is structured in accordance with ISO 11649, The issuer should be specified with the text 'ISO'		
2.237	Type	+++++++Tp	[1..1]	Component	Provides the type of the creditor reference.	C			
2.238	CodeOrProprietary	+++++++CdOrPrtry	[1..1]	Component	Coded or proprietary format creditor reference type.	C			
2.239	Code	+++++++Cd	[1..1]	Code	Coded creditor reference type.	C			Eg. SCOR for reference payments.
2.240	Proprietary	+++++++Prtry	[1..1]	Max35Text	Creditor reference type not available in a coded format.	C			Filled with info from incoming posting.
2.241	Issuer	+++++++Issr	[0..1]	Max35Text	Identification of the issuer of the credit reference type.	C			ISO is used when reporting ISO 11649 reference (RF Creditor reference)

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
2.242	Reference	++++++Ref	[0..1]	Max35Text	Unique and unambiguous reference assigned by the creditor to refer to the payment transaction.	C	DK: OCR-reference: For Payment Slip payments the OCR-reference is a combination of the former Payment Slip Code and Payment Id with a forward slash separator (eg. 71/123456789012345). For Payment Slip Codes not supporting Payment Id only the Payment Slip Code will be reported (eg. 73/). Creditor account reference/Giro account number is populated under the CreditorAccount object as an Other account number.		The reference according to the payment instrument. If ISO is used in 2.261 then the RF Creditor reference will be stated her.
2.245	AdditionalRemittanceInformation	+++++AddtlRmtInf	[0..3]	Max140Text	Additional information, in free text form, to complement the structured remittance information.	C			Filled with info from incoming posting.
2.246	RelatedDates	++++RltdDts	[0..1]	Component	Set of elements identifying the dates related to the underlying transactions.	C	EPC recommendation for SEPA transaction reporting		
2.247	AcceptanceDate Time	+++++AcptncDtTm	[0..1]	ISODateTime	Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent (debtor's agent in	C	SEPA Additional Optional Service		Payment date and time Time is always 01.01.01.000001 Example: 2010-10-

Danske Bank interpretation of the BankToCustomerDebitCreditNotificationV02

Common Global Implementation (CGI)

BankToCustomerDebitCreditNotificationV02 - camt.054.001.02

ISO Index No.	Item	Tag name	Mult.	Type	ISO Definition	Codes	CGI rules	Country Specific interpretation	Danske Bank comments
					case of a credit transfer, creditor's agent in case of a direct debit). This means - amongst others - that the account servicing agent has received the payment order and has applied checks as eg, authorization, availability of funds.				18T01.01.01.000001
2.273	ReturnInformation	++++RtrInf	{0..1}	Component	Set of elements specifying the return information.	C	Report when available for return items		
2.284	Reason	+++++Rsn	{0..1}	ChoiceComponent	Specifies the reason for the return.	C			
2.285	Code	++++++Cd	{1..1}			C			Returns and Direct Debit reason codes
2.306	AdditionalInformation	+++++AddtlInf	{0..1}	Max105Text	Provides further information	C			